



Phone: 724-715-7266 • Fax: 724-715-7341 • www.kimestech.com

JALPON[™] 5300 & 5300 FAST DRY High Solids, Firmer Film Rust Preventive Compounds

GENERAL DESCRIPTION

Jalpon[™] 5300 and 5300FD (Fast Dry) are high solids, lower VOC, moderately formulated rust preventive concentrates comprised of gelled calcium sulfonate and other components that yield a relatively tack-free coating. The high non-volatiles and lower viscosities of these products makes for easier handling compared to other high viscosity products.

TYPICAL PROPERTIES (NOT SPECIFICATIONS)

		J5300	J5300FD
Non-Volatile, Wt. %	ASTM D2369	70	70
Viscosity, Brookfield #5 @ 10 rpm, cP	ASTM D2196	10,000 - 25,000	5,000 - 20,000
Flash Point, °F (°C)	ASTM D93	>100 (>38)	>100 (>38)
Density, Pounds per Gallon @ 15.6°C	ASTM D1475	8.1	8.1

APPLICATIONS

Jalpon[™] 5300 and 5300FD are good rust preventives offering extended salt fog performance (AS[™] B117). They can be used as ballast tank coatings, truck chassis coatings, long-term storage of parts, aircraft OEM, maintenance coatings, and can also be used to coat farm implements. Jalpon[™] 5300 and 5300FD are both effective at holding rust in check when applied over existing rust (as long as it is not flaking). When used on mower decks, Jalpon[™] 5300 and 5300FD helps prevent grass build up on the deck in addition to keeping it free of rust. Jalpon[™] 5300 and 5300FD are REACh registered.

AVAILABILITY

Jalpon[™] 5300 and 5300FD are available in 55-Gallon Open Head Drums.

10-28-2019